

GRÄSHOPPA // PENDANT, EU MODEL

GROSSMAN COLLECTION

Designed by Greta Grossman

PRODUCT



COLORS



DESCRIPTION

The iconic Gräshoppa shade is fixed with a brass tube and brass fittings on the top. For mounting on the ceiling, the pendant is equipped with a steel bracket covered by a half round sphere canopy in brass and a brass tube. Shade is powder-coated and are available in 4 colours.

VERSION - GRÄSHOPPA PENDANT

RAL codes are indicative.

- Jet Black / White inside // RAL 9005 / RAL 9003 // Gloss level 20 / Gloss level 20
- Anthracite grey / White inside // RAL 7016 / RAL 9003 // Gloss level 20 / Gloss level 20
- Blue grey / White inside // RAL 160 60 05 / RAL 9003 // Gloss level 20 / Gloss level 20
- Matt white / White inside // RAL 9003 / RAL 9003 // Gloss level 20 / Gloss level 20
- Vintage red / White inside // RAL 3012 / RAL 9003 // Gloss level 20 / Gloss level 20
- Andorra red / White inside // RAL 020 30 20 / RAL 9003 // Gloss level 17 / Gloss level 20
- Oyster white/ White inside // RAL 1013 / RAL 9003 // Gloss level 17 / Gloss level 20

Fabric wire White: // Blue grey // Mat White

Fabric wire Black: // Jet Black // Anthracite grey // Vintage red // Andorra red // Oyster white

VERSION

Order item - look for part number in the pricelist.

Series contains the following:

- GM1 GRÄSHOPPA**
- GM2 COBRA TABLE**
- GM3 COBRA FLOOR**
- GRÄSHOPPA TASK TABLE LAMP**
- GRÄSHOPPA PENDANT**
- COBRA WALL LAMP**



FACTS

MATERIAL

Shade: Powder-coated steel

Canopy: Brass

Swivel: Solid brass

MEASUREMENT - L x W x H mm

Lamp height: 353 mm

Lamp stand: 375 x 435 mm

Canopy diameter: Ø80 mm

Canopy length: 131 mm

Shade height: 230 mm

Shade diameter: Ø150 mm

Cable length, exposed: APP. 2500 mm

WEIGHT ITEM - LAMP INCL. WIRE

684 g

PACKAGING TYPE

Cardboard box

PACKAGING MEASUREMENT - L x W x H cm

L: 45 x W: 21 x H: 21 cm

WEIGHT PACKAGING - MATERIAL TYPE (recyclable)

- LD-EPE foam: 20 g

- EPE bag: 8 g

- PE polybag: 6 g

- Cardboard inside: 231 g

- Cardboard outside, 5ply Corrugated: 532 g

WEIGHT INCL. PACKAGING - TOTAL

1481 g

NUMBER OF PARCELS

1 pcs.

ACCESSORIES

Mounting parts: screw 2pcs (4g); rawlplug 2pcs (1g); Allen key 1pcs (1g).

ENVIRONMENT

-

TESTS

-

CERTIFICATION AND LABELS

CE-CERTIFIED


SAFETY INSTRUCTIONS

If the cord or plug is damaged, unplug it from the socket with dry hands. Do not use the lamp until it is

LIGHT SOURCE:

- Socket: E14 base

- Bulb types recommended:



- Recommended light sources:

If LED is chosen, only dimmable versions work.

470 Lumen (~ 40W incandescent ~
30W halogen ~ 4-6W LED)

- Max. light output for above lamps:

470 Lumen (~ 40W incandescent ~
30W halogen ~ 4-6W LED)

- Best result is achieved with frosted light bulbs

with a CRI (Colour Rendering Index) larger than 90.

- Lightbulb not included.

*Euro voltage: 230 V

*Frequency: 50 Hz

*Supply voltage: AC power ~

*Normally Closed: IP20



CE-Mark



Class II / Double insulated



Luminaires accepted for mounting on a flammable base