


## frame



powder coating

**black**

[1 Colors](#)



powder coating

**white**

[1 Colors](#)



metal

**stainless steel**

[1 Colors](#)

## seat



wood

**blanched oak**


[1 Colors](#)



wood

**black open pore**

[1 Colors](#)



lacquered

**white lacquered**

[1 Colors](#)



metal

**stainless steel**

[1 Colors](#)

## soft-leather



P1



### Application

Contract and domestic use.

### Description

Thickness 0,9 / 1,0 mm

European raw hides

Chrome tannage

Through-dyeing Aniline

Finishing pigmented

## Test

This item complies with 3M test for oleo and hydro repellency.

The Scotchgard treatment gives more protection and durability to leather.

Dry rub fastness

UNI EN ISO 11640 > 3 Grey Scale

Light fastness

UNI EN ISO 105-B02 > 3 Blue Scale

Tear resistance

UNI EN ISO 3377-1 > 20 N

Flame resistance

BS EN 1021-2:2006

No Ignition

BS EN 1021-1:2006

No Ignition

## Care



Dust with a soft and dry cloth for the normal cleaning. Stains can be treated with a wet cloth or cotton wool and with products for the cleaning initially more delicate like neutral soap or cleansing milk. Dry immediately after treatment. Never use abrasive or aggressive products like solvents, stain removers. Never steam it. Don't use shoe cleaning products. When a new product is used for cleaning, apply it in a "hidden" area test its effectiveness and to avoid damages where more visible. Avoid placing leather away from heat sources. Dust regularly with a soft and dry cloth.



EPD\*



Colors are purely indicative