



Counter stool with upholstered seat, solid beech wood spindle backrest and frame.

0.22 m³ 5.64 kg
7.77 Ft 12.43 Lbs

	Backrest height	Seat height	Width	Depth
Measures (mm)	895	660	470	470

- Frame** Solid beech legs and interior frame.
- Seat** Beech plywood covered with flexible flame retardant polyurethane foam with density between 25 kg/m³ and 40 kg/m³.
- Back** Solid beech spindles.
- Accessories** Polypropylene, felt or steel glides.
- Other materials** Zinc-nickel electrolyte screws. Galvanized screws. Polyvinyl acetate glue.

Fabrics / Telas

- 1** Soft-fiber
Jacquard One
Jacquard Three
Citadel
Sand
Era
Gravity
Rivet
Urban
- 2** Jacquard Two
Solid & Stripes
Loom One
Circular One Pure Eco
- 3** Jacquard Four
Medley
Revive 1
Natte
Main Line Flax
Loom Two
Mezzo

- 4** Jacquard 4 Special
Nexus
Field 2
Floyd
Remix 3
Heritage
Savane
Loom Three
Loom Four
Cura
Oceanic
- 5** Silk
Synergy
Step
Step Melange
Blazer
Melange Nap
Glow
Chili
Noma
Re-wool

- 6** Go check
Swing
Chartres
Loom Five
Zori
Patio
- 7** Canvas 2
Rime
Select
Clara 2
- 8** Capture
Fiord 2
Tonus 4
Divina 3
Lopi
Domino
- 9** Divina MD
Divina Melange 3
Hallingdal 65
Steelcut Trio 3

Faux Leather / Ecopiel

- 1** Valencia
2 Silvertex
3 Maglia
4 Dolce
8 Ultraleather Original
Ultraleather Linen
Ultraleather Pearlized
- 9** Brisa Original
Brisa Distressed
Brisa Fresco
Brisa Mokume
Ultraleather Cora Outdoor
Ultraleather Pony
Ultraleather Pro
Ultraleather Promessa
Ultraleather Promessa Outdoor
Ultraleather Dwell
Ultratech EcoTech
- 10** Brisa Distressed Outdoor
Ultraleather Distressed Outdoor
Ultratech Helix
Ultratech Wired


- 11** Ultraleather Reef Pro
Ultraleather Volar Bio
Ultratech Cove

Upholstery

Leather / Piel

- L1** High grade cow leather
Piel de vaca de 1ª categoría
- L3** Polished full grain leather
Plena flor pulida
- L6** Aniline leather batique-effect.
Scandinavian cattle.
Piel anilina efecto batique.
Ganado escandinavo.

Leather



Leather finish



Wood finish Beech

Premium finish and wood lacquers



RESISTANCE AND QUALITY UNE-EN 16139:2013
ISO 9001

FIREPROOF UNE-EN 1021-1:2006
B.S. 5852 Part 2 Crib V
UNI 9175 M-1
California Tech.Bulletin 117
BKZ 5.2

SUSTAINABILITY FSC
ISO 14001
level® 2 certified to ANSI/BIFMA e3 Standard